



Product Features and Specifications

- Rifled aluminum tubing, enhanced aluminum fins.
- Air pressure tested at 500 psi, leak tested with helium, then sealed and nitrogen pressurized.
- Inlet and outlet dimensions are identical (without end caps).
- Externally mounted flowrater body with Schrader valve for hiss-testing or internally mounted factory installed TXV.
- Refrigerant lines exit from the top of the coil.
- Three-piece service door.
- Embossed galvanized cabinets standard. (OEM painted cabinet available.)
- Fully insulated cabinets with faced insulation.
- Heavy duty plastic drain pan with four 3/4" FPT condensate drains (two per side).
- AHRI certifiable with all brands of A/C and feat pump systems.
- ETL listed for use with R-22, R-410A, R-454A, and R-32 when proper metering device is used.
- Ten-year limited warranty. For complete warranty details, please visit www.AspenMfg.com



Representative image only. Some models may vary in appearance. Due to continuous product improvement, specifications are subject to change without notice.

COIL MODEL	NOMINAL CAPACITY (BTUs)	R 410-A PISTON SIZE	DIMENSIONS					SHIPPING INFORMATION		
			CABINET DEPTH (A")	CABINET DE PTH (B")	CABINET HEIGHT (C")	INSIDE WIDTH (D")	INSIDE HEIGHT (E")	SHIPPING WEIGHT (LBS)		SKID QTY
								3 ROW	4 ROW	
CX24A*	24,000	0.055	21	22	14-1/2	20	13-1/2	35	39	16
CX24B*		0.055	21	22	15	20	14	37	42	16
CX24E*		0.055	21	27	17-1/2	20	16-1/2	50	57	16
CX30A*	30,000	0.059	21	22	15	20	14	37	42	16
CX30E*		0.059	21	27	17-1/2	20	16-1/2	50	57	16
CX36A*	36,000	0.068	21	22	15	20	14	37	42	16
CX36B*		0.068	21	27	17-1/2	20	16-1/2	47	53	16
CX36C*		0.068	21	22	17-1/2	20	16-1/2	41	47	16
CX36E*		0.068	21	27	21	20	20	56	65	12
CX42C*	42,000	0.074	21	27	21	20	20	58	67	12
CX42D*		0.074	21	32	21	20	20	65	74	6
CX48A*	48,000	0.080	21	27	17-1/2	20	16-1/2	49	56	16
CX48B*		0.080	21	27	21	20	20	56	64	12
CX48C*		0.080	21	27	21	20	20	56	65	12
CX48D*		0.080	21	32	21	20	20	66	75	6
CX60A*	60,000	0.089	21	27	21	20	20	58	67	6
CX60B*		0.089	21	32	21	20	20	66	75	6
CX60C*		0.089	21	32	24-1/2	20	23-1/2	77	90	6
CX60D*		0.089	21	32	25	20	24	79	91	6
CX60E*		0.089	21	32	25	20	24	82	95	6

DRAIN PAN TEMPERATURE TABLE	
DRAIN PAN TYPE	TEMP LIMITS
Plastic - Standard	290°
Plastic - High Temp	425°
Metal - High Temp	600°

CX Spec-2024-09-V002

In keeping with its commitment to continuous improvement, Aspen Manufacturing reserves the right to make changes without notice and incurring obligation.