



Product Features and Specifications

- Rifled aluminum tubing, enhanced aluminum fins.
- Air pressure tested at 500 psi, leak tested with helium, then sealed and nitrogen pressurized.
- Inlet and outlet dimensions are identical (without end caps).
- Externally mounted flowrater body with Schrader valve for hiss-testing or internally mounted factory-installed TXV.
- Refrigerant lines exit from the top of the coil.
- Three piece service door.
- Embossed galvanized cabinets standard. (OEM painted cabinet available.)
- Fully insulated cabinets with faced insulation.
- Heavy duty plastic drain pan with four 1/2" FPT condensate drains (two per side).
- AHRI certifiable with all brands of A/C and heat pump systems.
- ETL listed for use with R-22, R-410A, R-454A, and R-32 when proper metering device is used.
- Ten-year limited warranty. For complete warranty details, please visit www.AspenMfg.com.

Representative image only. Some models may vary in appearance. Due to continuous product improvement, specifications are subject to change without notice.

COIL MODEL	NOMINAL CAPACITY (BTUs)	DIMENSIONS					SHIPPING INFORMATION			
		CABINET			INSIDE		SHIPPING WEIGHT (LBS)		SKID QTY	
		DEPTH (A")	DEPTH (B")	HEIGHT (C")	WIDTH (D")	HEIGHT (E")				
DX24A*	24,000	21	22	14-1/2	20	13-1/2	35	39	16	
DX24B*				15		14	37	42		
DX24E*				17-1/2		16-1/2	50	57		
DX30A*	30,000		22	15		14	37	42		
DX30E*			17-1/2	16-1/2		50	57			
DX36A*			22	15		14	37	42		
DX36B*	36,000		27	17-1/2		16-1/2	47	53		6
DX36C*			22				41	47		
DX36D*			32				56	65		
DX36E*	42,000		27	21		20	58	67		12
DX42C*			32	65		74	6			
DX42D*			27	17-1/2		16-1/2	49	56		16
DX48A*	48,000	21		20	56	64	12			
DX48B*					65	75				
DX48C*			32		66	75				
DX48D*	60,000	27	32	23-1/2	58	67	6			
DX60A*		24-1/2			66	75				
DX60B*					25	77		90		
DX60C*	24		24-1/2	79	91					
DX60D*		25	82	95						
DX60E*		23-1/2	69	79						
DX60F*										

DRAIN PAN TEMPERATURE TABLE	
DRAIN PAN TYPE	TEMP LIMITS
Plastic - Standard	290°
Plastic - High Temp	425°
Metal - High Temp	600°

DX Spec-2024-11-V002

In keeping with its commitment to continuous improvement, Aspen Manufacturing reserves the right to make changes without notice and incurring obligation.