



### Product Features and Specifications

- Rifled aluminum tubing, enhanced aluminum fins.
- Air pressure tested at 500 psi, leak tested with helium, then sealed and nitrogen pressurized.
- Liquid line - 3/8" OD, suction line - 1/4" OD on 1-1/2- 3 ton and 7/8" OD on 3-1/2 - 5 ton.
- Refrigerant lines exit from the top of the coil with Schrader valve for hiss-testing.
- Three-piece access doors on top of the coil for easy service.
- Fully insulated cabinet with plenum sides and back constructed of foil-backed, faced, one-inch thick, fiberglass duct board.
- Heavy duty plastic pan with 4-3/4" NPT condensate drains on each side of the coil.
- Secondary metal drain pan included with one inch spacing around the cabinet for turnkey installation.
- AHRI certifiable with all brands of A/C and heat pump systems.
- ETL listed for use with R-22, R-410A, R-454A, and R-32 when proper metering device is used.
- Ten-year limited warranty with registration. For complete warranty details, please visit [www.AspenMfg.com](http://www.AspenMfg.com)

Representative image only. Some models may vary in appearance. Due to continuous product improvement, specifications are subject to change without notice.

COIL MODEL	NOMINAL CAPACITY (BTUs)	R 410-A PISTON SIZE	DIMENSIONS					SHIPPING INFORMATION		
			CABINET DEPTH (A")	CABINET DE PTH (B")	CABINET HEIGHT (C")	INSIDE WIDTH (D")	INSIDE HEIGHT (E")	SHIPPING WEIGHT (LBS)		SKID QTY
								3 ROW	4 ROW	
DX24A*	24,000	0.055	21	22	14-1/2	20	13-1/2	35	39	16
DX24B*		0.055	21	22	15	20	14	37	42	16
DX24E*		0.055	21	27	17-1/2	20	16-1/2	50	57	16
DX30A*	30,000	0.059	21	22	15	20	14	37	42	16
DX30E*		0.059	21	27	17-1/2	20	16-1/2	50	57	16
DX36A*	36,000	0.068	21	22	15	20	14	37	42	16
DX36B*		0.068	21	27	17-1/2	20	16-1/2	47	53	16
DX36C*		0.068	21	22	17-1/2	20	16-1/2	41	47	16
DX36D*		0.068	21	32	21	20	20	56	65	6
DX36E*		0.068	21	27	21	20	20	56	65	12
DX42C*	42,000	0.074	21	27	21	20	20	58	67	12
DX42D*		0.074	21	32	21	20	20	65	74	6
DX48A*	48,000	0.080	21	27	17-1/2	20	16-1/2	49	56	16
DX48B*		0.080	21	27	21	20	20	56	64	12
DX48C*		0.080	21	27	21	20	20	56	65	12
DX48D*		0.080	21	32	21	20	20	66	75	6
DX60A*	60,000	0.089	21	27	21	20	20	58	67	6
DX60B*		0.089	21	32	21	20	20	66	75	6
DX60C*		0.089	21	32	24-1/2	20	23-1/2	77	90	6
DX60D*		0.089	21	32	25	20	24	79	91	6
DX60E*		0.089	21	32	25	20	24	82	95	6
DX60F*		0.089	21	32	24-1/2	20	23-1/2	69	79	6

DP Spec-2024-09-V002

In keeping with its commitment to continuous improvement, Aspen Manufacturing reserves the right to make changes without notice and incurring obligation.

DRAIN PAN TEMPERATURE TABLE	
DRAIN PAN TYPE	TEMP LIMITS
Plastic - Standard	290°
Plastic - High Temp	425°
Metal - High Temp	600°

DP Spec-2024-09-V002

In keeping with its commitment to continuous improvement, Aspen Manufacturing reserves the right to make changes without notice and incurring obligation.