



Product Features and Specifications

- Rified copper tubing, enhanced aluminum fins.
- Immersion-tested at 500 psi, then nitrogen-pressurized and sealed.
- Left or right-hand refrigerant and plumbing connections.
- Liquid line - 3/4" ODS, suction line - 3/4" ODS on 1-1/2 3 ton and 7/8" ODS on 3-1/2 - 5 ton.
- Externally mounted flowrater body with Schrader valve for hiss-testing.
- Heavy duty plastic drain pans on most models, powder coated galvanized steel horizontal drain pans standard on all.
- Upflow, horizontal right, ior horizontal left without field modification. Downflow applications require plate kit, sold seperately.
- AHRI certifiable with all brands of A/C and heat pump systems.
- ETL listed for use with R-22, R-410A, R-454A, and R-32 when proper metering device is used.
- Ten-year limited warranty. For complete warranty details, please visit www.AspenMfg.com

Customization

- Factory or field-installed TXV available.
- Painted cabinets.
- Powder-painted metal or stainless pans.
- Schrader mounted on suction manifold, external to cabinet.

Downflow Kit Part Numbers

- **METAL DRAIN PANS** 16" DWNFLWM-16 & 18" DWNFLWM-18
- **PLASTIC DRIAN PANS** DWNFLWP

Unit shown with service panels removed. Representative drawing only. Some models may vary in appearance. Duct opening dimensions can be ascertained by subtracting 1-1/2" for top opening width/depth, 3/4" for bottom opening.

| COIL MODEL | NOMINAL CAPACITY (BTUs) | DIMENSIONS | | | | SHIPPING INFORMATION | | | |
|------------|-------------------------|-------------------------|-----------|------------|-------------|-----------------------|-------|-------|----------|
| | | CABINET | | | | SHIPPING WEIGHT (LBS) | | | SKID QTY |
| | | MIN WIDTH | MAX WIDTH | DEPTH (D)" | HEIGHT (H)" | 2 ROW | 3 ROW | 4 ROW | |
| CE24A* | 24,000 | 14 | 23 | 21-1/2 | 19 | 31 | 39 | 46 | 20 |
| CE24B* | | | | | | 36 | 45 | 54 | |
| CE24C* | | | | | 23 | 41 | 52 | 61 | 12 |
| CE24D* | | | | | | 46 | 58 | 69 | |
| CE30A* | 30,000 | 14 | 23 | 21-1/2 | 19 | 36 | 45 | 54 | 20 |
| CE30B* | | | | | | 41 | 52 | 61 | |
| CE30C* | | | | | 23 | 46 | 58 | 69 | 12 |
| CE30D* | | | | | | 52 | 65 | 77 | |
| CE30E* | 36,000 | 14 for 2, 3R; 17 for 4R | 23 | 21-1/2 | 23 | 54 | 67 | 79 | 10 |
| CE36A* | | | | | | 41 | 52 | 61 | |
| CE36B* | | | | | 27 | 46 | 58 | 69 | 12 |
| CE36C* | | | | | | 52 | 65 | 77 | |
| CE36D* | 27 | 57 | 71 | 84 | 10 | | | | |
| CE36F* | | 30 | 67 | 84 | | 100 | | | |
| CE42A* | 42,000 | 17 | 26-1/2 | 21-1/2 | 23 | 46 | 58 | 69 | 12 |
| CE42B* | | | | | | 27 | 52 | 65 | |
| CE42C* | | | | | 57 | | 71 | 84 | 10 |
| CE42D* | | | | | 30 | 62 | 78 | 92 | |
| CE48A* | 48,000 | 17 | 26-1/2 | 21-1/2 | 27 | 52 | 65 | 77 | 12 |
| CE48B* | | | | | | 30 | 57 | 71 | |
| CE48C* | | | | | 62 | | 78 | 92 | 10 |
| CE48D* | | | | | 67 | | 84 | 100 | |
| CE48F* | | | | | 64 | | 80 | 94 | |
| CE48G* | | | | | 69 | 86 | 102 | | |

CE Spec-2024-11-V002

In keeping with its commitment to continuous improvement. Aspen Manufacturing reserves the right to make changes without notice and incurring obligation.

| COIL MODEL | NOMINAL CAPACITY (BTUs) | DIMENSIONS | | | | SHIPPING INFORMATION | | | |
|------------|-------------------------|--------------------|-----------|--------------------|---------------------|-----------------------|-------|-------|----------|
| | | CABINET WIDTH (W)" | | CABINET DEPTH (D)" | CABINET HEIGHT (H)" | SHIPPING WEIGHT (LBS) | | | SKID QTY |
| | | MIN WIDTH | MAX WIDTH | | | 2 ROW | 3 ROW | 4 ROW | |
| CE60A* | 60,000 | 20-1/2 | 26-1/2 | 21-1/2 | 30 | 62 | 78 | 92 | 10 |
| CE60B* | | | | | | 67 | 84 | 100 | |
| CE60C* (3) | | | | 23 | | 70 | 88 | 104 | |
| CE60D* (3) | | | | | | 76 | 95 | 112 | |
| CE60F* | | | | 21-1/2 | | 64 | 80 | 94 | |

| DRAIN PAN TEMPERATURE TABLE | |
|-----------------------------|-------------|
| DRAIN PAN TYPE | TEMP LIMITS |
| Plastic - Standard | 290° |
| Plastic - High Temp | 425° |
| Metal - High Temp | 600° |

CE Spec-2024-11-V002

In keeping with its commitment to continuous improvement, Aspen Manufacturing reserves the right to make changes without notice and incurring obligation.