



Unit shown with service panels removed. Representative drawing only. Some models may vary in appearance. Duct opening dimensions can be ascertained by subtracting 1-1/2" for top opening width/depth, 3/4" for bottom opening.

Product Features and Specifications

- Rifled copper tubing, enhanced aluminum fins.
- Immersion-tested at 500 psi, then nitrogen-pressurized and sealed.
- Left or right-hand refrigerant and plumbing connections.
- Liquid line - 3/4" ODS, suction line - 3/4" ODS on 1-1/2 3 ton and 7/8" ODS on 3-1/2 - 5 ton.
- Externally mounted flowrater body with Schrader valve for hiss-testing.
- Heavy duty plastic drain pans on most models, powder coated galvanized steel horizontal drain pans standard on all.
- Upflow, horizontal right, or horizontal left without field modification. Downflow applications require plate kit, sold separately.
- AHRI certifiable with all brands of A/C and heat pump systems.
- ETL listed for use with R-22, R-410A, R-454B, and R-32 when proper metering device is used.
- Ten-year limited warranty. For complete warranty details, please visit www.AspenMfg.com

Customization

- Factory or field-installed TXV available.
- Painted cabinets.
- Powder-painted metal or stainless pans.
- Schrader mounted on suction manifold, external to cabinet.

Downflow Kit Part Numbers

- | | |
|-------------------------|---------------------------|
| METAL DRAIN PANS | PLASTIC DRAIN PANS |
| • 16" DWNFLWM-16 | • DWNFLWP |
| • 18" DWNFLWM-18 | |

COIL MODEL	NOMINAL CAPACITY (BTUs)	CABINET DIMENSIONS				SHIPPING INFORMATION				
		MIN. WIDTH	MAX. WIDTH (W)"	DEPTH (D)"	HEIGHT (H)"	WEIGHT (LBS)			SKID QTY	
						2 ROW	3 ROW	4 ROW		
CE24A*	24,000	14	23	21-1/2	19	31	39	46	20	
CE24B*					36	45	54			
CE24C*					23	41	52	61	12	
CE24D*						46	58	69		
CE30A*	30,000	14	23	21-1/2	19	36	45	54	20	
CE30B*					23	41	52	61		
CE30C*						27	46	58	69	12
CE30D*					52		65	77		
CE30E*					54		67	79		
CE36A*	36,000	14 for 2, 3R; 17 for 4R	23	21-1/2	23	41	52	61	12	
CE36B*					27	46	58	69		
CE36C*						30	52	65	77	10
CE36D*					57		71	84		
CE36F*					67		84	100		
CE42A*	42,000	17	26-1/2	21-1/2	23	46	58	69	12	
CE42B*					27	52	65	77		
CE42C*						30	57	71	84	10
CE42D*					62		78	92		
CE48A*	48,000	17	26-1/2	21-1/2	27	52	65	77	12	
CE48B*					30	57	71	84		
CE48C*						30	62	78	92	10
CE48D*							67	84	100	
CE48F*					64		80	94		
CE48G*					69		86	102		

COIL MODEL	NOMINAL CAPACITY (BTUs)	CABINET DIMENSIONS				SHIPPING INFORMATION			
		MIN. WIDTH	MAX. WIDTH (W)"	DEPTH (D)"	HEIGHT (H)"	WEIGHT (LBS)			SKID QTY
						2 ROW	3 ROW	4 ROW	
CE60A*	60,000	20-1/2	26-1/2	21-1/2	30	62	78	92	10
CE60B*				67		84	100		
CE60C* (3)				23		70	88	104	
CE60D* (3)				76		95	112		
CE60F*				21-1/2		64	80	94	

DRAIN PAN TEMPERATURE TABLE	
DRAIN PAN TYPE	TEMP LIMITS
Plastic - Standard	290°
Plastic - High Temp	425°
Metal - High Temp	600°

ASK FOR ASPEN

CE Spec-2024-12

In keeping with its commitment to continuous improvement, Aspen Manufacturing reserves the right to make changes without notice and incurring obligation.