



Representative image only. Some models may vary in appearance. Due to continuous product improvement, specifications are subject to change without notice.

### Product Features and Specifications

- Rifled copper tubing, enhanced aluminum fins.
- Immersion-tested at 500 psi, then nitrogen-pressurized and sealed.
- Left-hand refrigerant and plumbing connections, with downturn suction line for easy installation in manufactured housing applications.
- Downflow plates and manufactured housing drain hose included.
- Liquid line - 3/8" ODS, suction line - 3/4" ODS on 1-1/2 - 3 ton and 7/8" ODS on 3-1/2 - 5 ton.
- Liquid line Schrader valve for coil pressurization-confirmation testing.
- Heavy duty polypropylene drain pans.
- Drain connection: 177L pans have single LH 3/4" FPT, 195L pans have quad drains, 3/4" FPT.
- AHRI certifiable with all brands of A/C and heat pump systems.
- ETL listed for use with R-22, R-410A, R-454B, and R-32 when proper metering device is used.
- Ten-year limited warranty. For complete warranty details, please visit [www.AspenMfg.com](http://www.AspenMfg.com).

COIL MODEL	NOMINAL CAPACITY (BTUs)	DIMENSIONS			SHIPPING INFORMATION				
		PAN		COIL BARE SLAB HEIGHT (H)"	WEIGHT (LBS)			SKID QTY	
		WIDTH (W)"	DEPTH (D)"		2 ROW	3 ROW	4 ROW		
CM24A(2,3)*	24,000	17-3/4	19-5/8	13-1/2	17	27	N/A	30	
CM24B(2,3)*				15-1/2	20	31		25	
CM24C(2,3)*				17-1/2	23	36		20	
CM24D(2,3)*				19-1/2	25	40		20	
CM30A(2,3)*	30,000	17-3/4	19-5/8	15-1/2	20	31	N/A	25	
CM30B(2,3)*				17-1/2	23	36		20	
CM30C(2,3)*				19-1/2	25	40		20	
CM36A(2,3,4)*	36,000	17-3/4	19-5/8	17-1/2	23	36	47	25	
CM36B(2,3,4)*				19-1/2	25	40	53	20	
CM36C34*				N/A	23	26	N/A	25	N/A
CM42A(2,3)*	42,000	17-3/4	19-5/8	19-1/2	25	40	55	20	
CM42A4*			19-1/2	17-1/2	N/A	50	25		
CM48A3*	48,000	17-3/4	19-5/8	21-1/2	N/A	45	60	16	
CM48A4*			19-1/2						
CM48B3*			19-5/8	23-1/2		49	63	12	
CM48B4*			19-1/2						
CM48C3*			19-5/8						
CM48C4*			19-1/2	25-1/2		54	68		
CM48D3*			19-5/8						
CM48D4*			19-1/2	27-1/2		58	72		
CM48E3*			19-5/8	19-1/2		40	55	20	
CM48E4*									
CM59A4*	60,000	17-3/4 - 19-1/2	19-1/2	25-1/2	34	54	70	12	
CM60A3*		19-1/2			19-1/2	37	58		76
CM60A4*						38	60		79
CM60B3*						41	65		86
CM60B4*						27-1/2	46		73

Notes: Use metal drain pan on oil furnaces or other applications where outlet temperatures may exceed 290°F +/-5°F.

DRAIN PAN TEMPERATURE TABLE	
DRAIN PAN TYPE	TEMP LIMITS
Plastic - Standard	290°
Plastic - High Temp	425°
Metal - High Temp	600°

CM Spec-2024-12

In keeping with its commitment to continuous improvement, Aspen Manufacturing reserves the right to make changes without notice and incurring obligation.