



Representative image only. Some models may vary in appearance. Due to continuous product improvement, specifications are subject to change without notice.

Product Features and Specifications

- Rifled aluminum tubing, enhanced aluminum fins.
- Air pressure at 500 psi, leak tested with helium, then nitrogen-pressurized and sealed.
- Left or right-hand refrigerant and plumbing connections.
- Externally mounted flowrater body with Schrader valve for hiss-testing.
- Heavy duty plastic or metal drain pans.
- Upflow without field modification. Downflow applications require field kit, sold separately.
- AHRI certifiable with all brands of A/C and heat pump systems.
- ETL listed for use with R-22, R-410A, and R-32 when proper metering device is used.
- Ten-year limited warranty. For complete warranty details, please visit www.AspenMfg.com

Customization

- Factory or field-installed TXV available.
- Powder-painted metal or stainless pans.

Downflow Kit Part Numbers

- | | |
|-------------------------|---------------------------|
| METAL DRAIN PANS | PLASTIC DRAIN PANS |
| • 16" DWNFLWM-16 | • DWNFLWP |
| • 18" DWNFLWM-18 | |

COIL MODEL	NOMINAL CAPACITY (BTUs)	PAN DIMENSIONS						SHIPPING INFORMATION			
		WIDTHS (W)"				DEPTH (D)"	BARE SLAB HEIGHT (H)"	SHIPPING WEIGHT (LBS)			SKID QTY
		13	16	19-1/2	23			2 ROW	3 ROW	4 ROW	
DA24A*	24,000	13	16	19-1/2	23	19-3/8	13-1/2	11	16	21	30
DA24B*							15-1/2	12	18	24	
DA24C*							17-1/2	14	22	28	
DA24D*							19-1/2	15	24	32	
DA30A*	30,000	N/A	16	19-1/2	23	19-3/8	15-1/2	12	18	24	25
DA30B*							17-1/2	14	22	28	
DA30C*							19-1/2	15	24	32	20
DA30D*							21-1/2	17	27	35	16
DA36A*	36,000	13 for 2, 3R; 16 for 4R	16	19-1/2	23	19-3/8	17-1/2	14	22	28	25
DA36B*							19-1/2	15	24	32	
DA36C*							21-1/2	17	27	35	
DA36D*							23-1/2	19	29	38	
DA42A*	42,000	N/A	16	19-1/2	23	19-3/8	19-1/2	15	24	32	20
DA42B*							21-1/2	17	27	35	
DA42C*							23-1/2	19	29	38	
DA42D*							25-1/2	20	32	42	
DA48A*	48,000	N/A	16	19-1/2	23	19-3/8	21-1/2	17	27	35	16
DA48B*							23-1/2	19	29	38	
DA48C*							25-1/2	20	32	42	
DA48D*							27-1/2	22	35	46	
DA60A*	60,000	N/A	16	19-1/2	23	21-3/4	25-1/2	20	32	42	12
DA60B*							27-1/2	22	35	46	
DA60C*							24-1/2	25	39	52	
DA60D*							26-1/2	29	45	60	

*Notes: 1) Do not use plastic drain pans on oil furnaces or other applications where outlet temperatures may exceed 290 F. Specialty metal drain pans used for these applications. 2) Metal drain pan 3) For all coils – Liquid line 3/8 ODS; suction line 3/4" ODS for DA24-36, 7/8" for DA42-60"

DRAIN PAN TEMPERATURE TABLE	
DRAIN PAN TYPE	TEMP LIMITS
Plastic - Standard	290°
Plastic - High Temp	425°
Metal - High Temp	600°