



Unit shown with service panels removed. Representative photo only. Some models may vary in appearance. Duct opening dimensions can be ascertained by subtracting 1-1/2" for top opening width/depth, 3/4" for bottom opening.

Product Features and Specifications

- Rifled aluminum tubing, enhanced aluminum fins.
- Multi-stage leak testing with high pressure testing at 500 psi, mass spectrometer pressure decay with helium, then sealed and nitrogen pressurized.
- Left- or right-hand refrigerant and plumbing connections.
- Heavy duty plastic drain pans.
- Embossed galvanized cabinets standard with painted options to OEM color.
- Upflow standard; downflow with field-installed kit, sold separately.
- Cabinets fully insulated foil-faced insulation.
- Split access doors in front of cabinet for easy service access.
- AHRI certifiable with all brands of A/C and heat pump systems.
- ETL listed for use with R-22, R-410A, R-454B, and R-32 when proper metering device is used.
- Ten-year limited warranty. For complete warranty details, please visit www.AspenMfg.com

Customization

- Factory or field-installed TXV available
- High temperature plastic drain pan
- OEM color matched cabinets

Downflow Kit Part Numbers

- | | |
|-------------------------|---------------------------|
| METAL DRAIN PANS | PLASTIC DRAIN PANS |
| • 16" DWNFLWM-16 | • DWNFLWP |
| • 18" DWNFLWM-18 | |

COIL MODEL	NOMINAL CAPACITY (BTUs)	CABINET DIMENSIONS				SHIPPING INFORMATION			
		MIN. WIDTH	MAX. WIDTH (W)"	DEPTH (D)"	HEIGHT (H)"	WEIGHT (LBS)			SKID QTY
						2 ROW	3 ROW	4 ROW	
DC24A*	24,000	14	21	21-1/2	16	23	26	31	20
DC24B*						26	29	35	
DC24C*					20	30	36	40	16
DC24D*						34	40	46	
DC30A*	30,000	14	21	21-1/2	16	26	29	35	20
DC30B*						20	30	36	
DC30C*					24		34	40	46
DC30D*						36,000	14 for 2,3R; 17 for 4R	21	21-1/2
DC36A*	24	34	40	46	12				
DC36B*		28	39	44					
DC36C*	33		43	49	50				
DC36D*		42,000	17	24-1/2	21-1/2	20	34	40	46
DC42A*	24						39	44	41
DC42B*						28	43	49	50
DC42C*	33						44	53	61
DC42D*		48,000	17	24-1/2	21-1/2	24	39	44	41
DC48A*	28						43	49	50
DC48B*						33	44	53	61
DC48C*	38						48	60	65
DC48D*		60,000	21	24-1/2	21-1/2	28	44	53	61
DC60A*	33						48	60	65
DC60B*						38	51	65	72
DC60C* (2)	43						54	67	75
DC60D* (2)		48				12			

Notes: 1) Do not use plastic drain pans on oil furnaces or other applications where outlet temperatures may exceed 290 F. Specialty metal drain pans used for these applications.
2) Metal drain pan 3) For all coils – Liquid line 3/8 ODS; suction line 3/4" ODS for DC24-36, 7/8" for DC42-60.

DRAIN PAN TEMPERATURE TABLE	
DRAIN PAN TYPE	TEMP LIMITS
Plastic - Standard	290°
Plastic - High Temp	425°
Metal - High Temp	600°

DC Spec-2024-12

In keeping with its commitment to continuous improvement, Aspen Manufacturing reserves the right to make changes without notice and incurring obligation.