



Representative image only.
Some models may vary in appearance.



Product Features and Specifications

- Rified aluminum tubing, enhanced aluminum fins.
- Multi-stage leak testing with high-pressure testing at 500 psi, mass spectrometer pressure decay with helium, then sealed and nitrogen pressurized.
- Left- or right-hand refrigerant and plumbing connections.
- Externally mounted flowrator body with Schrader valve for hiss-testing.
- Heavy duty plastic drain pans standard.
- Embossed galvanized steel cabinets standard with painted options for OEM color.
- Upflow standard; downflow with field-installed kit, sold separately.
- Cabinets fully insulated foil-faced insulation.
- Split access doors in front of cabinet for easy service access.
- AHRI certifiable with all brands of A/C and heat pump systems.
- ETL listed for use with R-22, R-410A, R-454B, and R-32 when proper metering device is used.
- Ten-year limited warranty. For complete warranty details, please visit www.AspenMfg.com

Customization

- Factory or field-installed TXV available.
- High-temperature plastic drain pan.
- OEM color-matched cabinets.

COIL MODEL	NOMINAL CAPACITY (BTUs)	DIMENSIONS				SHIPPING INFORMATION			
		CABINET WIDTH (W)*		CABINET DEPTH (D)*	CABINET HEIGHT (H)*	SHIPPING WEIGHT (LBS)			SKID QTY
		MIN WIDTH	MAX WIDTH			2 ROW	3 ROW	4 ROW	
DE25A*	24,000	14	21	21-1/2	19	35	38	43	20
DE25B*						38	41	47	
DE25C*					23	42	48	52	16
DE25D*						46	52	58	
DE25E*						51	56	59	
DE31A*	30,000	14	21		19	38	41	47	20
DE31B*						23	42	48	52
DE31C*					46		52	58	12
DE31D*					51	56	59		
DE31E*	36,000	14 for 2, 3R; 17 for 4R	21		23	42	48	52	12
DE37A*						46	52	58	
DE37B*					27	51	56	59	
DE37C*						55	61	63	
DE37D*						30	56	65	
DE37E*	42,000	17	21		23	46	52	58	12
DE43A*				27		51	56	59	
DE43B*					55	61	63		
DE43C*				30	56	65	73	10	
DE43D*					60	72	77		
DE43E*	48,000	17	24-1/2	27	51	56	59	12	
DE49A*					30	55	61		63
DE49B*				56		65	73		
DE49C*				60	72	77			
DE49D*				35	66	79	87		
DE49E*	60,000	21	24-1/2	30	56	65	73	12	
DE61A*					35	63	72		77
DE61B*				75		82			
DE61C*				79	87				
DE61D*									

*Notes: 1) Do not use plastic drain pans on oil furnaces or other applications where outlet temperatures may exceed 290 F. Specialty metal drain pans used for these applications. 2) Metal drain pan 3) For all coils – Liquid line 3/8 ODS; suction line 3/4” ODS for DC24-36, 7/8” for DC42-60

DRAIN PAN TEMPERATURE TABLE	
DRAIN PAN TYPE	TEMP LIMITS
Plastic - Standard	290°
Plastic - High Temp	425°
Metal - High Temp	600°

ASK FOR ASPEN

DE HE Spec-2024-12

In keeping with its commitment to continuous improvement, Aspen Manufacturing reserves the right to make changes without notice and incurring obligation.