

Product Features and Specifications

- Rified aluminum tubing, enhanced aluminum fins.
- Air pressure tested at 500 psi, leak tested with helium, then sealed and nitrogen pressurized.
- Left- or right-hand refrigerant and plumbing connections.
- Externally mounted flowrator body with Schrader valve for hiss-testing.
- Heavy duty plastic or metal drain pans powder coated galvanized steel horizontal drain pans standard.
- Embossed galvanized steel cabinets standard. Cabinet feature furnace connectors.
- Upflow, horizontal right, and horizontal left without field modification. Downflow application require field kit, sold separately.
- Fully insulated foil-faced insulation.
- Split access doors in front of cabinet for easy service access.
- AHRI certifiable with all brands of A/C and heat pump systems.
- ETL listed for use with R-22, R-410A, R-454A, and R-32 when proper metering device is used.
- Ten-year limited warranty. For complete warranty details, please visit www.AspenMfg.com



Customization

- Factory or field-installed TXV available
- High-temperature plastic drain pan
- Painted cabinets

Representative image only. Some models may vary in appearance. Due to continuous product improvement, specifications are subject to change without notice.

COIL MODEL	NOMINAL CAPACITY (BTUs)	DIMENSIONS				SHIPPING INFORMATION				
		CABINET WIDTH (W)*		CABINET DEPTH (D)*	CABINET HEIGHT (H)*	SHIPPING WEIGHT (LBS)			SKID QTY	
		MIN WIDTH	MAX WIDTH			2 ROW	3 ROW	4 ROW		
DE24A*	24,000	14	21	21-1/2	19	38	41	46	20	
DE24B*						41	44	50		
DE24C*					23	45	51	55	16	
DE24D*						49	55	61		
DE24E*						54	59	62		
DE30A*	30,000	14	21	21-1/2	19	41	44	50	20	
DE30B*						23	45	51		55
DE30C*					49		55	61		
DE30D*					27		54	59	62	
DE30E*						58	64	66		
DE36A*	36,000	14 for 2, 3R; 17 for 4R	21	21-1/2	23	45	51	55	12	
DE36B*						49	55	61		
DE36C*					27	54	59	62		
DE36D*						58	64	66		
DE36E*						30	59	68		76
DE42A*	42,000	17	24-1/2	21-1/2	23	49	55	61	12	
DE42B*						27	54	59		62
DE42C*					58		64	66		
DE42D*					30		69	68		76
DE42E*						63	75	80		12

Notes: 1) Do not use plastic drain pans on oil furnaces or other applications where outlet temperatures may exceed 290 F. Specialty metal drain pans used for these applications. 2) Metal drain pan 3) For all coils - Liquid line 3/8 ODS; suction line 3/4" ODS for DC24-36, 7/8"

COIL MODEL	NOMINAL CAPACITY (BTUs)	DIMENSIONS				SHIPPING INFORMATION						
		CABINET WIDTH (W)"		CABINET DEPTH (D)"	CABINET HEIGHT (H)"	SHIPPING WEIGHT (LBS)			SKID QTY			
		MIN WIDTH	MAX WIDTH			2 ROW	3 ROW	4 ROW				
DE48A*	48,000	17	24-1/2	21-1/2	27	54	59	62	12			
DE48B*						58	64	66				
DE48C*					30	59	68	76				
DE48D*						63	75	80				
DE48E*	60,000	20-1/2			24-1/2	21-1/2	35	69		82	90	12
DE60A*							30	59		68	76	
DE60B*								63		75	80	
DE60C*							35	66		78	85	
DE60D*	69	82	90									

DRAIN PAN TEMPERATURE TABLE

DRAIN PAN TYPE	TEMP LIMITS
Plastic - Standard	290°
Plastic - High Temp	425°
Metal - High Temp	600°