



Representative image only. Some models may vary in appearance. Due to continuous product improvement, specifications are subject to change without notice.

Product Features and Specifications

- Rifled aluminum tubing, enhanced aluminum fins.
- Multi-stage leak testing with high-pressure testing at 500 psi, mass spectrometer pressure decay with helium, then sealed and nitrogen pressurized.
- Left-hand refrigerant and plumbing connections, with downturn suction line for easy installation in manufactured housing applications.
- Downflow plates and manufactured housing drain hose included.
- Fully insulated cabinets with faced insulation.
- Liquid line - 3/8" ODS, suction line - 3/4" ODS on 1-1/2 - 3 ton and 7/8" ODS on 3-1/2 - 5 ton.
- Liquid line Schrader valve for coil pressurization-confirmation testing.
- Heavy duty polypropylene drain pans.
- Drain connection: 177L pans have single LH 3/4" FPT, 195L pans have quad drains, 3/4" FPT.
- AHRI certifiable with all brands of A/C and heat pump systems.
- ETL listed for use with R-22, R-410A, R-454B, and R-32 when proper metering device is used.
- Ten-year limited warranty. For complete warranty details, please visit www.AspenMfg.com.

COIL MODEL	NOMINAL CAPACITY (BTUs)	DIMENSIONS			SHIPPING INFORMATION		
		PAN		TOTAL COIL HEIGHT (H)"	WEIGHT (LBS)		SKID QTY
		WIDTH (W)"	DEPTH (D)"		3 ROW	4 ROW	
DM24A3*	24,000	17-3/4	19-5/8	13-1/2	18	N/A	30
DM24B3*				15-1/2	21		25
DM24E3*				13-1/2	18		30
DM24E4*					N/A	27	
DM36A3	36,000	17-3/4	19-5/8	17-1/2	49	N/A	25
DM36E3*					21		
DM42B3*	42,000	17-3/4	19-5/8	21-1/2	35	N/A	20
DM42E4					19-1/2		
DM48E3*	48,000			19-1/2	27	N/A	
DM59A4*	60,000	17-3/4 - 19-1/2	19-1/2		N/A	N/A	40
DM60A4*		19-1/2		23-1/2			46
DM60B4*				27-1/2			52

Notes: Use metal drain pan on oil furnaces or other applications where outlet temperatures may exceed 290°F +/-5°F.

DRAIN PAN TEMPERATURE TABLE	
DRAIN PAN TYPE	TEMP LIMITS
Plastic - Standard	290°
Plastic - High Temp	425°
Metal - High Temp	600°