NOMENCLATURE
Universal Evaporator Coil

D A 24 A3 D -145 L -400

① ② ③ ④ ⑤ ⑥ ⑦ ⑧

⑧ Option Code

⑦ Refrigerant and Plumbing Connections
L = left-hand plumbing and refrigerant connections
R = right-hand plumbing and refrigerant connections
T = refrigerant out the top, plumbing out opposite sides

⑥ Width Code
CA, DA, CM, DM Series = Drain pan width code
CC, CE, CP, CX, DC, DE, DP,
and DX Series = Furnace width code
CH Series = Cabinet width code

⑤ A2L Metering Device
D = non-bleed R32
J = non-bleed R454B
K = 20% bleed R454B
M = R32 piston
N = R454B piston

A1 Metering Device
4 = non-bleed A/C or H/P R410 TXV
6 = 20% bleed A/C or H/P R410 TXV
B = 20% bleed A/C or H/P R22 TXV
F = R-22 piston
G = R-410A piston
X = non-bleed A/C or H/P R22 TXV

④ Coil Descriptor Code (face area, rows, fpi)

③ Nominal Tonnage (MBTUH)

② Configuration
A = uncased up/down
C = cased up/down
E = cased multi-position VersaCoil
H = cased dedicated horizontal slab coil
M = manufactured home coil
P = cased dedicated horizontal with attached plenum
X = cased dedicated horizontal coil

① Series
C = C Series (Copper)
D = D Series (Aluminum)

In keeping with its commitment to continuous improvement. Aspen Manufacturing reserves the right to make changes without notice and incurring obligation.

UNIVERSALCOIL-NOMEN-2024-08-V02